


Standard screw **2.5~3mm** Air is automatically shut out when torque reaches a set value.



No. GT-S5TFG

5 Ball spring retainer

Push startup type/Noise reducer/Rear exhaust
 OP Torque Spring



No. GT-S5TG

6.35 Ball spring retainer

Adjust dial type Push startup type/Noise reducer/Rear exhaust
 OP Torque Spring


Standard screw **3~4mm** Air is automatically shut out when torque reaches a set value.



No. GT-S5TFB

5 Ball spring retainer

Push startup type/Noise reducer/Rear exhaust
 OP Torque Spring



No. GT-S5TB

6.35 Ball spring retainer

Adjust dial type Push startup type/Noise reducer/Rear exhaust
 OP Torque Spring


Standard screw **4~5mm** Air is automatically shut out when torque reaches a set value.



No. GT-S5TFR

5 Ball spring retainer

Push startup type/Noise reducer/Rear exhaust
 OP Torque Spring



No. GT-S5TR

6.35 Ball spring retainer

Adjust dial type Push startup type/Noise reducer/Rear exhaust
 OP Torque Spring

Torque Control Air Screwdriver, Impact Type

Standard screw **4.5~6mm** Combination between impact and torque control systems gives an excellent workability.

No. GT-S5TS

6.35 Bit sleeve retainer (Pull type)

Adjust dial type




| Model No. | Capacity Standard Screw (mm) | Torque Range (N·m) | No Load Speed (rpm) | Air Consumption (ml/min) | Hose Coupling | Overall Length (mm) | Weight (g) | Accessories | | | EDP No. |
|-----------|------------------------------|--------------------|---------------------|--------------------------|---------------|---------------------|------------|------------------|-------|----------|---------|
| | | | | | | | | Bit | Plug | L-wrench | |
| GT-S5TFG | 2.5~3.0 | 0.7~1.2 | 1,700 | 0.35 | Rc 1/8 | 243 | 860 | B36 Φ 2×70H | — | — | 311215 |
| GT-S5TG | 2.5~3.0 | 0.7~1.2 | 1,700 | 0.35 | Rc 1/4 | 260 | 920 | A14 Φ 2×65G | BPB-2 | — | 311212 |
| GT-S5TFB | 3.0~4.0 | 1.2~2.0 | 1,200 | 0.35 | Rc 1/8 | 243 | 830 | B36 Φ 2×70H | — | — | 311214 |
| GT-S5TB | 3.0~4.0 | 1.2~2.0 | 1,200 | 0.35 | Rc 1/4 | 260 | 910 | A14 Φ 2×65G | BPB-2 | — | 311211 |
| GT-S5TFR | 4.0~5.0 | 1.8~4.0 | 700 | 0.35 | Rc 1/8 | 243 | 850 | B36 Φ 2×70H | — | — | 311213 |
| GT-S5TR | 4.0~5.0 | 1.8~4.0 | 700 | 0.35 | Rc 1/4 | 260 | 930 | A14 Φ 2×65G | BPB-2 | — | 311210 |
| GT-S5TS | 4.5~6.0 | 3.9~9.8 | 6,500 | 0.25 | Rc 1/4 | 292 | 1,310 | A14 Φ 2×65G | BPB-2 | H3 | 324002 |

·Air pressure: 0.6MPa ·Air hose diameter: 6.35mm ·Overall length: Accessories and hanger parts not included. ·Weight: Accessories not included.
 ·Capacity is listed as instant reference and depends on operation conditions.

Bit installation anvil application

Unless otherwise mentioned, following type is a standard.

Standard type in Japan



※Option: Following retainer anvil is available.

