

Air Hose Reels (small)



Air Hose Reels
SHS-210A

6.5 mm 10m

- High-quality polyurethane hose.
- Easy coupling

Air Hose Reels
SHS-306

8.0 mm 6m

Model	Outlet hose				MPa	Inlet Hose		Dimensions (mm)			Weight (kg)
	I.D. (mm)	m	fittings	hose		m	Inlet	A	B	C	
SHS-210	6.5	10	Female G1/4	PU	1.4	0.8	Swivel Fitting Male R1/4	314	290	152	3.5
SHS-306	8.0	6	Female Rc3/8	PU	1.4	1.0	Swivel Fitting Male R3/8	314	290	152	3.5

Comes with mounting base set.

※inlet hose is not Anti-spark type.

Air Hose Reels (medium)



Air Hose Reel
SHR-31Z

8.0 mm 10m

Air Hose Reel
SHR-15Z

6.5 mm 15m

Air Hose Reel
SHR-35Z

8.0 mm 15m

Air Hose Reel
SHR-20Z

6.5 mm 20m

- High-quality polyurethane hose.
- Easy-changing coupling available.

Model	Outlet hose				MPa	Inlet hose		Dimensions (mm)			Weight (kg)
	I.D. (mm)	m	fittings	hose		m	fittings	A	B	C	
SHR-31Z	8.0	10	Female Rc3/8	PU	1.4	1.0	Swivel fitting male R3/8	408	384	173	6.4
SHR-35Z	8.0	15	Female Rc3/8	PU	1.4	1.0	Swivel fitting male R3/8	408	384	173	6.8
SHR-15Z	6.5	15	Female G1/4	PU	1.4	0.8	Swivel fitting male R3/8	408	384	173	7.0
SHR-20Z	6.5	20	Female G1/4	PU	1.4	0.8	Swivel fitting male R3/8	408	384	173	7.2

Comes with mounting base set.

※inlet hose is not Anti-spark type.

Outlet Cord Reels (small)(medium)



Outlet Cord Reel
SCS-310

100V 220V 10m

- Compact type triple outlet with a ground clip



Outlet Cord Reel
SLR-15N

100V 220V 15m

Outlet Cord Reel
SLR-20N

100V 220V 20m

Model	Wire		Outlet Cord		Power Rating		Inlet cord		Dimension (mm)			Weight (kg)
	Wire	m	Outlet		m		m	Inlet	A	B	C	
SCS-310	1.25 × 3	10	outlet w/ground clip		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	314	290	164	4.1
SLR-15N	1.25 × 3	15	outlet w/ground clip		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	408	384	183	7.7
SLR-20N	1.25 × 3	20	outlet w/ground clip		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	408	384	183	8.5

Comes with mounting base set.

Outlet Cord Reels with light (small)



Captain Light Reel
SCS-310C

100V 220V 10m

- Outlet Cord Reel with Captain light (18W hand light.)



Captain Light Reel
SCS-310D

100V 220V 10m

- Outlet Cord Reel with Captain light LED (18W LED hand light.)



Captain Light Reel
SLR-15CN

100V 220V 15m

Captain Light Reel
SLR-20CN

100V 220V 20m

- Outlet Cord Reel with Captain light (18W hand light.)

Captain Light Reel
SLR-15DN

100V 220V 15m

Captain Light Reel
SLR-20DN

100V 220V 20m

- Outlet Cord Reel with Captain light LED (18W LED hand light.)

Model	Wire		Cord		Power Rating		Inlet		Dimensions (mm)			Weight (kg)
	Wire	m	Outlet		m		m	Inlet	A	B	C	
SCS-310C	1.25 × 3	10	Hand light		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	314	290	164	4.5
SLR-15CN	1.25 × 3	15	Hand light		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	408	384	183	8.2
SLR-20CN	1.25 × 3	20	Hand light		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	408	384	183	8.9
SCS-310D	1.25 × 3	10	LED Hand light		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	314	290	164	4.5
SLR-15DN	1.25 × 3	15	LED Hand light		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	408	384	183	8.2
SLR-20DN	1.25 × 3	20	LED Hand light		AC125V/6A	AC250V/6A	0.8	plug (w/ground clip)	408	384	183	8.9

Comes with Mounting base set.

Water Reels



Water Reel
SWS-208

6.0 mm 8m

- Reliable PVC hose



Water Reel
SWR-310

8.0 mm 10m

- Reliable PVC hose

Model	Outlet Hose				MPa	Inlet Hose		Dimensions (mm)			Weight (kg)
	I.D. (mm)	m	Outlet	hose		m	Inlet	A	B	C	
SWS-208	6.0	8	Female G1/4 (w/O-ring)	PVC	1.4	0.8	Male R1/4	314	290	152	3.5
SWR-310	8.0	10	Female Rc3/8	PVC	1.4	1.0	Male R3/8	408	384	173	6.4

comes with mounting base set