

Fastening Tool

IMPACT DRIVER

Main Features

1. For various types of screws
2. Aluminum window sash
3. Furniture and other wooden applications.
4. Assembly for motorbikes and light vehicles
5. Disassembly/fixing of fenders, bumpers, and interiors.



1/4" (6.35mm) HEX.

KW-50S

KW-50S		
Drive Size	1/4" Hex	6.35 mm
Free Speed	10,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Recommended Torque	—	
Length (w/o socket)	7-1/4 in.	184.0 mm
Weight (w/o socket)	1.7 lbs.	0.77 kg
Air Consumption (normal)	2.1 c.f.m.	0.20 ml/min
Hose Size	1/4 in.	6.5 mm

Double Hammer



For Super Soft Joint

Performance figures are at 0.62MPa(90PSI) air pressure.

1/4" (6.35mm) HEX.

KW-50H

KW-50H		
Drive Size	1/4" Hex	6.35 mm
Free Speed	10,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Recommended Torque	—	
Length (w/o socket)	7-1/4 in.	184.0 mm
Weight (w/o socket)	1.7 lbs.	0.77 kg
Air Consumption (normal)	2.1 c.f.m.	0.20 ml/min
Hose Size	1/4 in.	6.5 mm

Double Hammer



For Soft Joint

Performance figures are at 0.62MPa(90PSI) air pressure.

1/4" (6.35mm) HEX.

KW-50

KW-50		
Drive Size	1/4" Hex	6.35 mm
Free Speed	10,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Recommended Torque	1.5-20 ft-lb	2-27 Nm
Length (w/o socket)	7-1/4 in.	184.0 mm
Weight (w/o socket)	1.7 lbs.	0.77 kg
Air Consumption (normal)	2.1 c.f.m.	0.20 ml/min
Hose Size	1/4 in.	6.5 mm

Double Hammer



For Hard Joint

Performance figures are at 0.62MPa(90PSI) air pressure.

1/4" (6.35mm) HEX.

KW-7PD

KW-7PD		
Drive Size	1/4" Hex	6.35 mm
Free Speed	8,800 r.p.m.	
Impact Per Min.	2,500 i.p.m.	
Recommended Torque	7-50 ft-lb	10-70 Nm
Length (w/o socket)	5-15/16 in.	150.0 mm
Weight (w/o socket)	2.2 lbs.	1.0 kg
Air Consumption (normal)	10.6 c.f.m.	0.30 ml/min
Hose Size	1/4 in.	6.5 mm



Double Hammer

Performance figures are at 0.62MPa(90PSI) air pressure.

1/4" (6.35mm) HEX.

KW-5PD

KW-5PD		
Drive Size	1/4" Hex	6.35 mm
Free Speed	8,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Recommended Torque	1.5-20 ft-lb	2-27 Nm
Length (w/o socket)	6-5/16 in.	160.0 mm
Weight (w/o socket)	1.7 lbs.	0.75 kg
Air Consumption (normal)	7.1 c.f.m.	0.20 ml/min
Hose Size	1/4 in.	6.5 mm

Double Hammer



Performance figures are at 0.62MPa(90PSI) air pressure.